



SERVICE INSTRUCTIONS

1-800-KEATING • keatingofchicago.com

INSTALLATION OF ROUND REPLACEMENT LIGHTS IN PRE-2000 TS FRYERS

Instructions:

1. Turn the equipment off and disconnect from power source.
2. Open the control panel to allow access to wiring. Make note of which wires go to which lights, use the equipment wiring diagram as a reference.
3. Disconnect all wire quick-connect terminals from existing lights.
4. Remove all switches and related hardware and hole plug if used.
5. Remove and discard old lights, instruction plate, and backing plate.
6. Assemble the new backing plate 062999 (place on inside of control panel), instruction plate, switches (leave nuts loose temporarily), and hole plug (if used).
7. Insert all the new lights from the front in the order as shown.
8. Align backing plate and instruction plate so that they are flush with mating surfaces.
9. Tighten switch nuts and hardware.
10. Cut quick-connect terminals from existing wire harness light wires (cut close to terminal). Make sure to keep wires that were common to a terminal together.
11. Strip insulation of each harness wire back 3/8".
12. Using the supplied wire nuts (blue), combine all the light wires according to their original hook-ups. Refer to the equipment wiring diagram. **NOTE: The new light red wire may be connected to either of the original connection wires. Connect the black to other of the original connection wire(s).**
13. Route and tie-wrap the new light wires neatly, taking care not to damage the light in-line resistor (250V lights only).
14. Re-assemble control panel to unit.
15. Reconnect power source.
16. Turn fryer on and test to insure that all lights are functioning properly.

